GUANGZHOU GRANDVIEW CREATIVE TECHNOLOGY CO., LTD

A: No.1 Building of No.43 South International Trade Avenue, Hualong Town,Panyu District, Guangzhou China.

T: 86-20-84899499 F: 86-20-84805299

W: www.grandviewscreen.com

Grandview Website



Fancy Series II

Tab-Tension Motorized Screen

16:9 /16:10 220" Ultra-Wide Visual Experience for Home and Commercial Spaces

Design Philosophy

The Fancy II Series carries forward the minimalist aesthetics of the first-generation model, adhering to the design philosophy of “refinement through simplicity.” When retracted, the screen’s bottom bar neatly seals the opening of the casing, creating a unified, elegant appearance. The smooth lines not only enhance visual appeal but also provide functional protection against dust, insects, and moisture.

Fancy II integrates advanced performance with forward-thinking design. Its clean, modern form factor blends effortlessly into a wide range of environments—from private residences to commercial venues and customized interior installations. Equipped with Grandview’s newly engineered 45W DC motor, it supports 100–240V global input, features built-in electromagnetic shielding for strong anti-interference performance, and operates with less than 50dB noise. The motor is rated for over 20,000 operational cycles.

An exclusive S-curve acceleration and deceleration algorithm ensures smooth, quiet transitions during extension and retraction. This intelligent motion profile eliminates sudden jerks, minimizes vibration, and prevents excessive tension on the screen fabric, thereby protecting internal components and extending product lifespan.




Available Casing Colors
White/Black (Custom Order Only)

Core Advantages




Variable-Frequency Low-Noise Motor

* 100–240V wide voltage
* Smooth acceleration & deceleration
* Precise electronic travel control
* Built-in anti-interference shielding
* 20,000+ cycles
* <50 dB



Multiple Smart Control Options

Supports RS-485/RS-232, dry contact, 433MHz RF, infrared, and 12V trigger.



Crease-Free Screen Design

A specially designed roller tube features a stepped profile and a gradually tapered spiral structure to prevent pressure marks at the starting edge of the screen fabric during retraction, ensuring a smooth, flat viewing surface.




Dual-Layer Spring-Loaded Bottom Bar

* Multiple spring connection points allow the dual-layer bottom bar to flexibly compensate for dimensional tolerances, ensuring a precise, flush closure.
* The dual-layer structure provides enhanced rigidity and resistance to deformation, maintaining screen flatness and ensuring long-lasting durability.



Fully Enclosed Housing Design


The fully enclosed housing combines a sleek, minimalist appearance with effective protection against dust and insects. It prevents contaminants from reaching the screen fabric, keeping the viewing surface clean over time.




Flexible Installation Options

The housing features an integrated sliding mounting channel with adjustable L-shaped brackets, allowing flexible positioning and easy installation in a variety of residential environments.


Product Specifications



Front View



A Casing Side View



B Casing Side View

Aspect Ratio	Diagonal Measurement	Viewing Area (W×H) mm	Black Drop (B3) mm	Lower Border (B2) mm	Left/Right (B1) mm	Product Height (A) mm	Product Length (L) mm	Model A/B
16:9	92"	2037×1146	600	25	27	1934	2233	B
	100"	2214×1245	600	25	27	2033	2410	B
	106"	2347×1320	600	25	27	2108	2543	B
	110"	2435×1370	600	25	27	2158	2631	B
	120"	2656×1494	600	25	27	2282	2856	B
	133"	2944×1656	600	25	35	2444	3160	B
	150"	3321×1868	600	50	60	2726	3920	A
	165"	3653×2055	600	50	60	2913	4252	A
	180"	3985×2241	600	50	60	3099	4584	A
	200"	4428×2491	600	50	60	3349	5027	A
	220"	4870×2740	600	50	60	3598	5469	A
16:10	94"	2037×1273	600	25	27	2061	2233	B
	103"	2214×1384	600	25	27	2172	2410	B
	109"	2347×1467	600	25	27	2255	2543	B
	113"	2435×1522	600	25	27	2310	2631	B
	123"	2656×1660	600	25	27	2448	2856	B
	137"	2944×1840	600	25	35	2628	3160	B
	165"	3554×2221	600	50	60	3079	4153	A
	180"	3877×2423	600	50	60	3281	4476	A
	200"	4308×2692	600	50	60	3550	4907	A
	220"	4739×2962	600	50	60	3820	5338	A

● UST fabric standard with NO left & right borders.

Compatible Screen Fabrics

WW5
Standard Throw PS White

UHD130
Standard Throw PS White

GG3
Standard Throw PS Grey

DY3
Black Grid UST ALR

DY4
Standard Throw ALR

DY7
Standard Throw ALR

DY10
Standard Throw ALR